Red-D-Arc Welderentals

Calibration Certificate

Unit Serial Number: MB010057G Date Tested: 02-02-17

Instrument Number: 97487 Mac Address: 00:0A:8D:01:7C:CF

IP Address: 192.168.111.222

| Primary Standard | | | | | | | |
|------------------|-------------------|---------------------|-------------------|---------------------|-------------------|---------------------|--|
| | 382 (F) | | 882 (F) | | 1382 (F) | | |
| | Signal Voltage | Recorder display | Signal Voltage | Recorder display | Signal Voltage | Recorder display | |
| Channel 1 | 2.790 | 382 | 6.016 | 882 | 9.240 | 1382 | |
| Channel 2 | 2.799 | 383 | 6.019 | 883 | 9.244 | 1383 | |
| Channel 3 | 2.800 | 383 | 6.025 | 883 | 9.246 | 1383 | |
| Channel 4 | 2.803 | 384 | 6.025 | 883 | 9.253 | 1384 | |
| Channel 5 | 2.809 | 384 | 6.031 | 883 | 9.256 | 1384 | |
| Channel 6 | 2.809 | 384 | 6.039 | 885 | 9.263 | 1385 | |

Allowable difference in temp reading is +or- 5 Deg. F.

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 1897018

Calibration Date: 11-04-16

Precision digital multimeter SN: US36049893

Calibration Date: 11-04-16

ProHeat 35 power supply used for signal output SN: MC100331G

Calibration date: 02-01-17

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

| Unit passed inspection. | X | Technician: | Jared Lamar |
|-------------------------|----------|-------------|-------------|
| Calibration due date: | 02-02-18 | | Signature |